

# XL-CP99A36x

Part No: various

## ExpertSystem XL

## Safety edge / Contact profile

This datasheet provides technical data about single parts of the ExpertSystem XL safety edge family. Safety edges (also called sensors) are part of pressure-sensitive edge systems according to EN ISO 13856-2. A pressure-sensitive edge system consists of a safety edge and a control unit and its intended use is for pressure-sensitive protection systems.

### Contact profile data

Designation / Art. No.	XL-CP99A / 389087
Dimensions in mm (Tolerances acc. to DIN ISO 3302-1 tl. E2)	H 99 x W 44
Contact profile material	EPDM, non-conductive, black
Hardness	70 Shore A (+/- 5)
Switching contact material	EPDM, conductive
Delivery length	max. 25 m
Weight per meter	1.28 kg/m

### Mounting profiles data

Designation	XL-AP36	XL-AP3620	XL-AP36Q	XL-AP3620Q
Art. No.	402163	409585	412006	412008
Material / Finish	Al / nature	Al / anod. black	Al / nature	Al / anod. black
Weight per meter	0.36 kg/m	0.45 kg/m	0.33 kg/m	0.42 kg/m
Delivery length	max. 6.1 m			

### Safety edge data

Designation / Art. No.	XL-CP99A36x / various, see brochure
Single sensor, length (min. / max.)	0.3 m / 20 m
Cable length, max.	40 m
Combined single sensors: max. number / sensor length in total / cable length in total	4 sensors / 20 m / 40 m
Mounting orientations	All orientations
Effective sensing surface (Figure A)	X = 59 mm / Z = 40 mm $\alpha = 150^\circ$ / L = sensor length
Actuating distance / Pre-travel (A / 200mm/s)*	< 3 mm
Actuating force (A / 200mm/s)*	< 40 N
Overtravel at 250 N (B1)*	> 67 mm
Overtravel at 400 N (B2)*	> 69 mm
Total travel at 600 N (C)*	> 74 mm
Operating temperature	-20°C to 60°C
Switching cycles	> 10'000
Degree of protection	IP67
Max. voltage	24 V ACDC
Continuous current load at max. voltage	10 mA
Actuation resistance (typical / max.)	50 - 150 Ohm / 500 Ohm
Standards	EN ISO 13856-2 / EN 12978
EC type examination certificate No.	E 7195 (Suva)

\* Acc. to EN ISO 13856-2; Test piece  $\varnothing$  80 mm; Test location c3; Test speed (A) 200 mm/s; Temp. 20°C  
The actuating force and the deformation travels depend on the response time of the used signal processing unit. If the integrated radio transmitter XRF-TI is used, the overtravel and total travel values are reduced by 8mm, where the XRF-TI is located.

